

Liquid Wax

Liquid cleaning and maintenance wax, made from high quality natural waxes, such as natural beeswax, carnauba and candelilla wax. For parquet, wooden and natural stone floors







Application: This product cleans, protects and nourishes wooden floors, furniture, beams, waxed doors, natural stone, rustic tiles, Burgundy stone, etc.

- Does not alter the colour of natural stone;
- Dissolves old layers of dirty wax;
- Adds a new depth of colour to old waxed floorboards:
- Easy to apply without any seams;
- Can be applied mechanically or by hand.

Instructions

Surface preparation: The surface must be dry, clean and free of dust.

Product preparation: Shake well before use. Keep the product at room temperature for at least 1 day before application. Do not heat!

Application: Use a wax applicator, paintbrush and/or rotating machine fitted with a red pad. Apply DevoNatural Liquid Wax generously to the floor, using a wax applicator or mop. Allow to take effect for 10 - 15 minutes. Then remove any old dissolved wax using cloths. However, do not dry the floor completely. Continue to work with the rotating machine fitted with thick red or black pads, in order to remove any remaining wax residues. Then clean and dry the floor using cloths. Finally, polish the floor again, if required, using a rotating machine fitted with a thick white pad.

Drying time: 12 hours at room temperature

Finish: If required, highly absorbent porous floors can be post-treated after 12 hours, by applying DevoNatural Solid Wax. For the application method, see the DevoNatural Solid Wax technical data sheet.

Working temperature: Optimal workable at room temperature

Consumption: 5 - 10 m²/litre

Clean tools: Using turpentine or white spirit

Maintenance: Clean the floor while dry, using a vacuum cleaner or duster. Do not use a damp mop! Extra wax should occasionally be applied to areas where people frequently walk, using DevoNatural Solid Wax or DevoNatural Liquid Wax. So that your floor lasts longer, wax regularly using a machine fitted with a thick white or cotton pad.

Shelf life: Minimum 24 months if kept in properly sealed packaging at room temperature

Disposal: Any left-over product should be handled as chemical waste and properly disposed of, in compliance with local regulations.



Liquid Wax

Technical properties

Description (type): Liquid cleaning wax for maintaining waxed floors

Base: Natural beeswax, carnauba wax, candelilla wax, silicone resin, white spirit and turpentine. Aliphatic and

aromatic hydrocarbons

Characteristic properties: Dissolves old layers of dirty wax and re-protects the floor. Can also be used to remove marks left behind

after waxing.

Application:

Surface: The surface must be dry, clean and free of dust.

Material temperature: 20°C
Air humidity: 40 - 70%

Material moisture content:

Product preparation: Shake well before use. Keep at room temperature for at least 1 day before application. Do not heat!

Pot life: Not applicable

Application: Using a wax applicator, paintbrush and/or rotating machine fitted with a thick red or white pad

Diluent/Cleaning liquid:

Consumption/covering power:

Coat thickness:

DevoNatural Diluent
5 - 10 m²/litre
Not applicable

Physical and chemical properties:

Colour(s): Transparent/whitish
Odour: Turpentine, conventional wax
Consistency: Thick liquid at room temperature.

Dynamic or kinematic viscosity at 20 °C: > 20 sec 4 mm Method: DIN53211

Specific weight 20°C/density: 0.88 g/cm³

Solids by weight: 11 % Method: calculation VOC content: 89.0 % organic solvents Method: calculation

Drying at 20°C/65% HR: 12 hours at room temperature. Fully dry after: 12 hours, remains workable

Gloss (H. 60°): Depending on application, up to high gloss

pH at 20°C:

Water soluble at 20 °C:

Vapour pressure/20°C, mBar:

Flash point:

< 55°C

Spontaneous combustion temperature:

Not applicable

Shear strength:

Not applicable

Shelf life: Unlimited at room temperature, if kept in properly sealed packaging

Safety: Inflammable. May cause irritation to the respiratory tracts. May cause sensitivity if it comes into contact with

the skin. Harmful to organisms living in water and likely to cause harmful long-term effects to aquatic environments. Repeated exposure may cause the skin to become dry and cracked. Inhalation of vapours may cause drowsiness and dizziness. Avoid contact with the skin. If the product comes into contact with the eyes, wash immediately with lots of water and consult a specialist. Wear suitable gloves. If adequate ventilation is not possible, wear appropriate breathing apparatus. Only use in well ventilated areas. Avoid any discharge of the product into the environment. Consult the special instructions/safety data sheet. Do not inhale the vapours.

Contains: Turpentine, oil

 $\textbf{Symbol:} \ \mathsf{Irritant} \, / \, \, \textbf{Symbol:} \, \, \mathsf{Harmful} \, \, \mathsf{to} \, \, \mathsf{the} \, \, \mathsf{environment}$

For further information, see the safety information sheet (MSDS).

Environmental information:

Bio-degradable: N

Disposal: Any left-over product should be handled as chemical waste and properly disposed of, in compliance with the

local regulations.

Delivery/Transport:

Available packaging(s): 1 litre

© Devomat Industries NV - rev. 2014-09-01a

Please note: This information is based on many years of experience and research. As we are unable to influence the application method, we cannot accept any responsibility on the basis of this information.