



## Easy Colour

Plant-based stain in aqueous phase for parquet and wood floors. Easy Colour is easy to apply and compatible with all DevoNatural finish products.



**Applications:** DevoNatural Easy Colour is particularly recommended for easy staining and adding a contemporary look to all types of parquet and wood floors, furniture, interior doors, etc. Only suitable for indoor use.

- Seamless finish;
- Easy to apply;
- Compatible with the entire DevoNatural range, including High Solid Oil, Wax and any DevoNatural varnish products;
- Fast drying;
- Wide range of colours;
- “Bio-based”: plant-based product
- Penetrates fully into the wood
- The coloured pigment does not fade if lacquers in aqueous phase are used.
- Higher viscosity for easy application as an industrial finish.

## Instructions

### Preparing the surface:

**Treated or tarnished wood:** If necessary, strip, sand and/or thoroughly clean in order to open the pores.

**New or cleaned wood:** Fine and smooth sanding. In both cases, the surface must be clean and free of grease.

**Preparing the product:** Shake thoroughly before use, regularly stir the product during application.

**Application:** Using a brush, cotton cloth or single-brush machine equipped with a thick white or beige pad. Apply enough product so that the wood is saturated. Leave to act for a few minutes. Immediately remove any excess product using lint free cotton cloths or polish with a rotating machine equipped with a thick white or beige pad. On parquet floors, if possible, apply with a paint roller in 60 - 80 cm strips. Immediately polish the strips using a rotating machine equipped with a thick white pad, using a sufficient amount of the product. Immediately wipe with a clean lint free cotton cloth and polish using a rotating machine with a thick white pad. Thoroughly polish the strips with a sufficient amount of product. If necessary, polish the entire floor again using a thick white pad, in order to remove all excess product. If desired, a second layer can be applied after 2 hours, in order to obtain a more pronounced colour. Within 2 hours of the product drying fully, it is possible to retouch colour differences by spraying a little water and wiping the floor with a white cloth or pad. Avoid exposing the floor to excessive heat or sunlight during application.

**Drying time:** 2 hours.

**Finish:** after it has dried for 4 hours, apply the 1<sup>st</sup> layer of DevoNatural finish without pre-sanding

**Walkable:** this depends on the finish. See the relevant DevoNatural product sheet.

**Application temperature:** do not apply at temperatures below 12 °C.

**Consumption:** 10 - 15 m<sup>2</sup>/litre.

**Clean tools:** with water.

**Shelf life:** 12 months in the original unopened packaging. Store away from frost.

**Waste disposal:** Unusable product residues should be considered chemical waste and must be disposed of according to the local public requirements.

EU limit value for this product (cat A/f): 150 g/l (2007)/130 g/l (2010). This product contains max. 3 g/l VOC.

**Important:** Before use, please shake the product and check the colour! Always test the colour on the floor that you intend to treat.

# Easy Colour

## Technical properties:

<b>Description (type):</b>	Plant-based stain in aqueous phase for parquet and wood floors
<b>Base:</b>	Combination of plant-based binders.
<b>Characteristic properties:</b>	Impregnation stain, odourless, in aqueous phase.
<b>Application:</b>	
Surface:	The surface must be dry, clean and free of grease.
Material temperature:	10 – 35 °C.
Air humidity:	40 - 70 %.
Material moisture content:	Depending on the type of wood, consistent with the air humidity. Oak: 9 - 11 % at 60 % RH.
Product preparation:	The product is ready to use after it has been shaken thoroughly.
Pot life:	Not applicable.
Application:	Use a brush or roller. Rub using a lint free cloth or single-brush machine equipped with a thick white pad.
Diluent/for cleaning:	Water.
Consumption/covering power:	10 – 15m <sup>2</sup> /litre per layer.
Layer thickness:	Not applicable (impregnation product).
Finish:	DevoNatural High Solid Oil, Hardwax Oil, Solid Wax, Finish, Transit or Passage
<b>Physical and chemical properties:</b>	
Colour(s):	Wide range of colours, custom colours also available.
Odour:	Little or none.
Consistency:	Liquid.
Dynamic or kinematic viscosity at 20 °C:	55 – 65 sec 2 DIN53211.
Specific weight at 20 °C/density:	1.01 – 1.06 kg/l – method: DIN 53217.
Solid matter by weight:	10 – 15 % - method: calculation.
VOC content:	2.9 g/L – method: calculation.
Drying at 20 °C/65 % RH:	Dust dry after approx. 2 hours. Application of 2 <sup>nd</sup> layer: after approx. 2 hours. Application of finish layer: after approx. 4 hours.
Fully hardened:	Not applicable.
Gloss (H. 60 °):	Not applicable.
pH at 20 °C:	8 – 9
Water soluble at 20 °C:	Yes.
Vapour pressure/20 °C, mBar:	Not applicable.
Flash point:	Not applicable.
Self-combustion at:	Not applicable.
Shear strength:	Not applicable.
Shelf life:	If protected against frost and kept in fully sealed packaging: 12 months minimum
<b>Safety:</b>	Important: Keep out of children's reach. In case you need to consult a doctor, keep the container or label at hand. Safety data sheet available on request.
<b>Environmental information:</b>	
Bio-degradable:	The product is not classified as harmful to the environment.
Waste disposal:	Product residues must be considered chemical waste and handled according to the applicable local public requirements.
<b>Delivery/transport:</b>	
Packaging:	100 ml and 1 litre.